

ALBANY INTL (ALB)(KALB) P (ARNG) 6 NW UTC-5(-4DT) N42°44.95' W73°48.12' **NEW YORK**
 285 B AOE Class I, ARFF Index C NOTAM FILE ALB H-101, 11C, 12K, L-32G, 33B, 34I
RWY 01-19: H8500X150 (ASPH-GRVD) S-140, D-200, 2D-400 PCN 70 F/C/X/T HIRL IAP, AD

CL 0.3% down N

RWY 01: MALSR. TDZL. PAPI(P4R)—GA 3.0° TCH 53'. RVR-TR

RWY 19: MALSR. PAPI(P4L)—GA 3.0° TCH 53'. RVR-TR Tree.

RWY 10-28: H7200X150 (ASPH-GRVD) S-140, D-200, 2D-400 PCN 67 F/C/X/T MIRL CL

RWY 10: REIL. Ground.

RWY 28: REIL. PAPI(P4L)—GA 3.22° TCH 53'. Thld dsplcd 1192'. Tree.

LAND AND HOLD—SHORT OPERATIONS

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 01	10-28	4150
RWY 28	01-19	3757

RUNWAY DECLARED DISTANCE INFORMATION

RWY 01: TORA-8500 TODA-8500 ASDA-8500 LDA-8500

RWY 10: TORA-7200 TODA-7200 ASDA-6780 LDA-6780

RWY 19: TORA-8500 TODA-8500 ASDA-8500 LDA-8500

RWY 28: TORA-7200 TODA-7200 ASDA-7200 LDA-6007

SERVICE: S4 FUEL 100LL, JET A OX3 FUEL (NC-100LL, A) FLUID HPOXR/B

AIRPORT REMARKS: Attended continuously. Birds, deer and other wildlife on and in/ovf arpt. Mowing within safety areas of all rwy's and twys May through Nov. Wx balloon launches approximately 3 miles south of arpt at 1100Z± and 2300Z±. Twy C west of Twy A non movement area. Twy D east of Rwy 01-19 rstd to acft 12,500 lbs and less. No acft parking between fire station and Twy L. Customs/Immigration's Flt Information Service located north end General Aviation apron. Acft clearing Customs utilize painted markings and proceed to minimize blast impact. Ldg fee. Flight Notification Service (ADCUS) avbl.

AIRPORT MANAGER: 518-242-2352

WEATHER DATA SOURCES: ASOS 120.45 (518) 464-6423. LLWAS. WSP.

COMMUNICATIONS: D-ATIS 120.45 UNICOM 122.95

RCO 122.2 (BURLINGTON RADIO)

Ⓡ **APP/DEP CON** 118.05 (194°-011°) 132.825 (011°-194°)

TOWER 119.5 **GND CON** 121.7 **CLNC DEL** 127.5 **NG OPNS** 30.1 (FM) 122.775 258.2

PDC

AIRSPACE: CLASS C svc ctc APP CON.

VOR TEST FACILITY (VOT) 108.2

RADIO AIDS TO NAVIGATION: NOTAM FILE ALB.

(L) (L) **VORTACW** 115.3 ALB Chan 100 N42°44.84' W73°48.19' at fld. 273/13W.

VOR unusable:

045°-065° byd 11 NM

066°-069° byd 11 NM blo 10,000'

078°-088° byd 20 NM blo 10,000'

109°-121°

121°-131° byd 30 NM

121°-131° wi 30 NM blo 9,900'

131°-168°

184°-189°

226°-269° byd 29 NM blo 15,000'

312°-315°

333°-343°

TACAN AZIMUTH unusable:

032°-042° byd 15 NM

164°-168°

303°-308° byd 37 NM

308°-333°

DME unusable:

303°-308° byd 37 NM

ILS/DME 109.5 I-DEJ Chan 32 Rwy 01. Class IIE.

ILS/DME 109.5 I-ALB Chan 32 Rwy 19. Class IB.

COMM/NAV/WEATHER REMARKS: Class C information avbl on ATIS frequency 20 NM.

ALBERT S NADER RGNL (See ONEONTA on page 235)