CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE ISP.

CALVERTON (L) (DH) VORW/DME 114.55 CCC Chan 92(Y) N40°55.78′ W72°47.93′ 137° 9.2 NM to fld. 85/13W.

VOR unusable:
055°–075°
233°–268° byd 25 NM
269°–290°

DME unusable:
056°–066° byd 39 NM

SUFFOLK CO (T) TACAN Chan 47 FOK (111.0) N40°50.27′ W72°37.91′ at fld. 50/13W. NOTAM FILE FOK.

TACAN unmonitored when twr clsd.

No NOTAM MP: 1600–2000Z‡ Mon

TACAN AZIMUTH unusable:
028°–038° byd 8 NM blo 3,500′
090°–155° byd 7 NM
335°–345° byd 7 NM blo 3,500′

ILS/DME 111.7 I–FOK Chan 54 Rwy 24. Class IT. Unmonitored when ATCT clsd.

WHEELER–SACK AAF (GTB)(KGTB) A 1 NE UTC–5(–4DT) N44°03.34′ W75°43.19′

MONTREAL
H–11C, 12K, L–32F
DIAP, AD

690 B TPA—See Remarks NOTAM FILE GTB Not insp.

RWY 03–21: H10000X150 (CONC) PCN 59 R/B/W/T HIRL

RWY 03: ALSF1. PAPI(P4L)—GA 3.0° TCH 64′. RVR–TR Thld dsplcd 1363′.

RWY 21: ALSF1. PAPI(P4L)—GA 3.0° TCH 72′. RVR–TR Rgt tfc.

RWY 15–33: H5002X144 (CONC) PCN 43 R/C/W/T HIRL

RWY 15: MALSR. RVR–TR Rgt tfc.

RWY 08–26: H4501X150 (ASPH–CONC) PCN 29 F/C/W/T LIRL

RWY 08: Rgt tfc.

SERVICE: **MILITARY— FUEL** Service–L–AOE JASU–3(ASU600–270–DDP). Fuel A++ (mil); Avbl 1400–0300Z‡ Mon–Fri, Exc hol, OT PN. **FLUID** SP De–ice Type I and Type IV avbl with 3 hr PN. **TRAN ALERT:** Opr 1400–1300Z‡ Mon–Fri; clsd Sat, Sun and Federal Hol ltd; no cathering, lav, trash removal, water, or crew trnsp svc avbl.

NOISE: Noise abatement Quiet hrs 0300–1100Z‡.

MILITARY REMARKS: Attended 1200–0300Z‡ Mon–Fri, clsd otr times PPR. Arpt clsd hols. See FLIP AP/1 Supplementary Arpt Information. Base Ops opr 1200–0400Z‡Mon–Fri; clsd Sat, Sun and Federal Hol. All tran acft inbd for prk ctc Base Ops 10 NM prior to ldg, mil aircrews must register with Base Ops if RON. Tran R/W prk south end of north ramp. Twy G, N, P, R and Twy L east of Twy B designated nonmovemant area. Acft inbd for Avn Fld Maint Act (AFMA) must arr no later 1900Z‡ ctc DSN 772–7536, C315–772–7536. Emerg ctc Mt Ops Cntr DSN 772–8620 C315–772–8620. **RSTD** PPR ctc Base Ops DSN 772–5681, C315–772–5681/5682. Tenant acft have priority for lcl pat ops, tran may be ltd. Rwy 15–33. Twy G rstd to C130 or smaller. Sod ldg/ops rstd to cntr, sod. Oasis rst to tenant R/W hot refuel ops, ldg/dep prohibited when clsd. Twy B btn Twy A and N ramp clsd. **CAUTION** UAS opr wi 20NM KGTB SFC–FL290. Extsy mil acft activity vcnty arpt mil acft refer to FLIP AP/1 prior to ops on Fort Drum or wi R–5201. Narrow Twy A, B, int arc 40′ wide. N Ramp edge lgt us. Twy B edge lgt us btn Twy A and Sabre helipad. W Ramp unlgtd. Rsc not mntn when base ops is clsd. Wildlife haz, refer to AP/1. **TFC PAT** TPA—Rotary wing 1400(710), fixed wing 2000(1310), turbojet 2500(1810), overhead 3000(2310). **CSTMS/AG/IMG** 24 hr PN, consult FCG. Aerial port msn acft plan arr btn 1300–0300Z‡ Mon–Fri exc hol, OT rqr advanced coord and apvl. **MISC** Wx svc avbl 24/7. DSN 772–6065, C315–772–6065. Back–up wx brief avbl fr 15 OWS Scott AFB DSN 576–9755/9702, C618–256–9755/9702. Pri wx sensors automated H24. Drg augmentation/back–up wx observation pt is obst 033°–162°. PMSV freq not monitored Sat, Sun and federal hol. ATC will assist in cooperative watch by notifying wx of unrprted cond. Rwy 09–8–26 cntr 75′ conc btn Rwy 03 and Twy D, PCN 54, remainder asph.

COMMUNICATIONS: ATIS 119.525

Ⓡ **APP/DEP CON** 124.875 307.125

TOWER 118.75 290.25 **GND CON** 123.45 229.8 **CLNC DEL** 123.65 **PMSV SACK METRO** 317.5

BASE OPS 126.2 233.7 **FORT DRUM FLT FLW** 141.025 319.25

AIRSPACE: CLASS D.

RADIO AIDS TO NAVIGATION: NOTAM FILE ART.

WATERTOWN (L) (L) VORTACW 109.8 ART Chan 35 N43°57.13′ W76°03.88′ 079° 16.2 NM to fld. 374/12W.

VOR unusable:
090°–111° byd 15 NM
112°–150°
151°–175° byd 20 NM

ILS/DME 108.5 I–AEZ Chan 22 Rwy 03.

ILS/DME 108.5 I–GTB Chan 22 Rwy 21. Class IE.

ASR/PAR
