AIRPORT/FACILITY DIRECTORY

GUAM

ANDERSEN N13°35.47′ E144°56.80′ NOTAM FILE PGUA. H-TACAN 111.7 UAM Chan 054 at Andersen AFB. 615/2E. No NOTAM MP Mon, Wed 2000–2300	HAWAIIAN-MARIAN DZ. P-1/
GUAM INTL (GUM)(PGUM) 3 NE UTC+10 N13°29.04´ E144°47.83´ 305 B LRA TPA—1307(1002)	HAWAIIAN-MARIAN
Class I, ARFF Index E NOTAM FILE GUM	IAP, AD
RWY 06L-24R: H12014X150 (ASPH-CONC-GRVD) S-135 D-235 2D-390 2D/2D2-780 PCN	69 F/B/X/U HIRL
RWY 06L: MALSR. PAPI(P4L)—GA 3.0° TCH 73´. Thid dspicd 1000´. 0.5% up. RWY 24R: PAPI(P4L)—GA 3.0° TCH 75´. Rgt tfc. 0.7% down.	
RWY 06R-24L: H10014X150 (ASPH-CONC-GRVD) S-135 D-235 2D-390 2D/2D2-780 PCN	69 F/B/X/U HIRI
RWY 06R: MALSR. PAPI(P4R)—GA 3.0° TCH 76′. 0.7% up.	
RWY 24L: PAPI(P4L)—GA 3.0° TCH 75'. Thid dsplcd 1004'. Hill. Rgt tfc. 0.5% down.	
RUNWAY DECLARED DISTANCE INFORMATION Rwy Ogl: Tora-12014 Toda-12014 ASDA-12014 Lda-11014	
RWY 06R: TORA-10014 TODA-10014 ASDA-10014 LDA-11014	
RWY 24L: TORA-9714 TODA-9714 ASDA-9714 LDA-8710	
RWY 24R: TORA-12014 TODA-12014 ASDA-12014 LDA-12014	
SERVICE: S2 FUEL 100LL, JET A1 0X 1, 2, 3 LGT Rwy 24L PAPI unusable byd 5° left of centerli	
AIRPORT REMARKS: Attended continuously. Rwy 06L24R less than 1000' overrun south end & 450' over 06 and Rwy 24 wind cone NSTD. Lighted tower 780' 1.3 NM east-northeast of Rwy 24L thld. Ris	
Rwy 24L thld 140' east of centerline extended +8'. Departing VFR acft maintain rwy heading unt	
of rwy and reaching 1000' AGL; right pattern 24L/R do not exceed 1500' AGL in tfc pattern. Class	
from making any turns onto or off Twy Golf (south) while utilizing Twy Echo. The first 500' of the left is not visible from the twr. Pilots are advised to caution for any presence of wildlife in that area. For	
on Twy K fronting the acft prkg apn from Gates 5-16 at the main trml, max taxing speed shall be no	
For the B747-8, dur Rwy 24L and 24R ops and due to jet blast effects at Gate 14, 16 and 18, the E	
from Gate 4 on Twy K to Twy J with the acft positioned on Twy J facing toward Rwy 24R. Dur taxiir	
Gates 5-16, all veh shall yield and remain clear of the veh tfc pat and are rstd to a max hgt of 14'. Fo	
airline will tow the acft into Gates 4 or 18 from Twy K and airline to provide wing-walkers as the ac Gates 4 or 18. ADG-VI airplanes may depart on Rwy 06L and Rwy 24R with acft on parallel Twy K a	
acft occupies the parallel twy byd 1500' of the point of tkof roll. For parking information all acft ctc	
dep terminal parking ctc ramp control for engine start and pushback. Tsnt acft prvd 24 hrs advn inf	o to Exec Mgr Guam
Intl Arpt Authority; 1–671–642–4455 Mon–Fri 2200–0700Z or Fax 1–671–646–8587. Customs	available 24 hours
daily. Landing fee. Consult special notice section of International NOTAMS. AIRPORT MANAGER : (671) 646–0300	
WEATHER DATA SOURCES: ASOS (671) 472–7399	
COMMUNICATIONS: ATIS 119.0	
(R) GUAM CERAP APP/DEP CON 119.8	
AGANA TOWER 118.1 GND CON 121.9 CLNC DEL 121.9 RAMP CON 121.6	
AIRSPACE: CLASS D svc Radio aids to navigation: Notam File HNL.	
NIMITZ (H) VORTACW 115.8 UNZ Chan 105 N13°27.27′ E144°44.00′ 063° 4.1 NM to fld.	674/2E.
VORTAC unusable:	
110°-130° byd 35 NM blo 3,000´. 200°-238° byd 14 NM blo 7,000´.	
MT MACAJNA NDB (HW) 385 AJA N13°27.21′ E144°44.22′ 061° 3.9 NM to fld. 658/2E.	
ILS/DME 110.3 I–GUM Chan 40 Rwy 06L.	
ILS/DME 110.9 I-AWD Chan 46 Rwy 06R. Class IE. DME unusable byd 15° right of course. ASR	
ASK COMM/NAV/WEATHER REMARKS: For radar advisory beyond 25 NM ctc Guam Center on 118.7. SSB receivin	g capability available
on all HF freq. Aeronautical Radio, Inc. (ARINC) see Associated Data.	
GUAM ARTCC (ZUA) (PGZU)	
118.7 119.8 120.5 121.5 remoted at Mount Santa Rosa. 118.4 remoted at Saipan.	P-1A
IT MACAJNA N13°27.21′ E144°44.22′ NOTAM FILE PGUM.	HAWAIIAN-MARIANA
NDB (HW) 385 AJA 061° 3.9 NM to Guam Intl. 658/2E.	P-1A
IIMITZ N13°27.27′ E144°44.00′ NOTAM FILE PGUM.	HAWAIIAN-MARIANA
(H) VORTACW 115.8 UNZ Chan 105 063° 4.1 NM to Guam Intl. 674/2E.	P-1A
VORTAC unusable	
110°-130° byd 35 NM blo 3,000′. 200°-238° byd 14 NM blo 7,000′.	
200 ⁻ -236 ⁻ byd 14 NNI bl07,000 .	