

TAMPA INTL (TPA)(KTPA) 6 W UTC-5(-4DT) N27°58.53' W82°32.00'

MIAMI
H-8H, L-21D, 24F
IAP, AD

26 B AOE LRA Class I, ARFF Index D NOTAM FILE TPA

RWY 01L-19R: H11002X150 (CONC-GRVD) S-60, D-210, 2S-175,

2D-358, 2D/2D2-850 PCN 85 R/B/W/T HIRL CL

RWY 01L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR

RWY 19R: MALS. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR Road.

RWY 01R-19L: H8300X150 (ASPH-CONC-GRVD) S-60, D-210,

2S-175, 2D-358, 2D/2D2-850 PCN 76 R/B/W/T HIRL CL

RWY 01R: REIL. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR

RWY 19L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 61'. RVR-TMR

RWY 10-28: H6999X150 (ASPH-CONC-GRVD) S-75, D-200, 2S-175,

2D-280, 2D/2D2-380 PCN 61 F/A/W/T HIRL

RWY 10: PAPI(P4L)—GA 3.0° TCH 42'. Thld dsplcd 498'. Railroad.

RWY 28: PAPI(P4L)—GA 3.0° TCH 50'. Trees.

LAND AND HOLD—SHORT OPERATIONS

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 19L	10-28	5650
RWY 28	01R-19L	4350

RUNWAY DECLARED DISTANCE INFORMATION

RWY 01L:TORA-11002 TODA-11002 ASDA-10800 LDA-10800

RWY 01R:TORA-8300 TODA-8300 ASDA-8300 LDA-8300

RWY 10: TORA-6999 TODA-6999 ASDA-6999 LDA-6501

RWY 19L:TORA-8300 TODA-8300 ASDA-8300 LDA-8300

RWY 19R:TORA-11002 TODA-11002 ASDA-11002 LDA-11002

RWY 28: TORA-6999 TODA-6999 ASDA-6501 LDA-6501

SERVICE: S4 FUEL 100LL, JET A OX 1, 2, 3, 4 LGT Rwy 10 PAPI unusbl 8° left and right of RCL.

AIRPORT REMARKS: Attended continuously. Bird act on and invof arpt. Rwy 10-28 not nmlly avbl to ops over 75,000 lbs GWT.

Rwy 10 first 2600' conc; Rwy 28 first 4400' asph. Only acft with prior pmsn may use trml apn; all otrs use GA apn.

Rwy 19L is noise sensitive to tbtj departures. Rwy 01R is noise sensitive to tbtj arrivals. Publd noise abatement procs in

efct. Rstrs to design Group V or Igr; Twy N west of Twy L and Twy E north of Twy J unavbl; Taxilane Z clsd to wingspan

gtr than 171 ft—PPR arpt ops. Twy F and Twy R are non-movement areas. Both locations are unavbl for Group IV acft

with a wingspan gtr than 117 ft w PPR fm arpt ops. Twy T PPR from arpt ops rqrd for acft with a wingspan gtr than 90

ft. Flight Notification Service (ADCUS) avbl.

AIRPORT MANAGER: 813-870-8700

WEATHER DATA SOURCES: ASOS 126.45 (813) 873-7228. LLWAS. TDWR.

COMMUNICATIONS: D-ATIS ARR 126.45 D-ATIS DEP 128.475 UNICOM 122.95

® APP/DEP CON 118.15 (001°-150°) 118.8 (220°-360°) 119.65 (151°-219°) 118.5

TOWER 119.5 GND CON 121.7 CLNC DEL 133.6

CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

RADIO AIDS TO NAVIGATION: NOTAM FILE PIE.

ST PETERSBURG (H) VORTACW 116.4 PIE Chan 111 N27°54.47' W82°41.06' 068° 9.0 NM to fld. 6/5W.

VOR unusable:

025°-054° byd 21 NM blo 5,000'

233°-250° byd 20 NM

TACAN AZIMUTH unusable:

133°-146°

COSME NDB (LOMW) 368 TP N28°05.13' W82°31.51' 189° 6.6 NM to fld. 41/5W. NOTAM FILE TPA.

ILS/DME 108.9 I-AMP Chan 26 Rwy 01L. Class IIIE.

LOC/DME 111.95 I-TWJ Chan 56(Y) Rwy 01R. LOC unusable byd 15° left of course. DME unusable byd 20° right of course.

ILS 110.3 I-TPA Rwy 19L. Class IIIE. LOM COSME NDB. LOC unusable byd 25° left of course.

ILS/DME 108.5 I-JRT Chan 22 Rwy 19R. Class ID.

