
EDWARDS AF AUX NORTH BASE (9L2) AF (NASA) 3 N UTC-8(-7DT) N34°59.45' W117°51.79' **LOS ANGELES**
 2299 NOTAM FILE EDW Not insp. **H-41, L-7C**
RWY 06-24: H5998X150 (ASPH) PCN 15 F/A/W/T HIRL **DIAF**
RWY 06: PAPI(P4L)—GA 3.0° TCH 50'.
RWY 24: PAPI(P4L)—GA 3.0° TCH 50'.
SERVICE: LGT ACTIVATE PAPI Rwy 06 and Rwy 24; HIRL Rwy 06-24—129.1
MILITARY REMARKS: Attended Mon-Fri 1400-0600Z, clsd weekends and holidays. **CAUTION** Rwy 06-24 has potential for hydroplaning dur and after rainfall events. Pilots use ctn when brkg dur wet rwy cond. **RSTD** PPR strictly enforced. Clsd to all tran acft without prior approval of 412 OG/CC. Due to rwy condition, all turns will occur on the conc areas of the rwy located at the apch end, dep end, and mid-fld. If unable to exit at center twy, acft must proceed to the dep end to initiate turn and exit mid-fld. Ltd to BE-20 type acft and smaller, 12,500 lbs or less. **MISC** Winds are estimated due to FMQ-13 wind sensors being accurate to within only +/- 4 Kt, issued estimated winds are for Main Base Rwy 04-22. ATC/Wx will not include/relay wind correction into forecast/phraseology. Therefore, aircrews will incorporate a +/- 4 Kt accuracy into their decision making process for flying opr. First 200' Rwy 06 and first 200' Rwy 24 conc. Mid 5598' of Rwy 06-24 is porous friction sfc exc for 300' conc cntr. Turnarounds pmtd on conc sfc only. Rwy 05L-23R mid 10000' porous friction sfc. First 1000' Rwy 05L and first 1000' 23R conc: mid 10000' porous friction sfc.
AIRPORT MANAGER: 805-277-1110
COMMUNICATIONS: (R) JOSHUA APP/DEP CON 133.65 348.7
TOWER 120.7 318.1 353.6
CLEARANCE DELIVERY PHONE: For CD ctc Joshua Apch at 661-277-3843.
RADIO AIDS TO NAVIGATION: NOTAM FILE EDW.
 (T) (T) VORTACW 116.4 EDW Chan 111 N34°58.94' W117°43.96' 263° 6.5 NM to fld. 2378/12E.
 TACAN AZIMUTH unusable:
 098°-158° byd 19 NM
 DME unusable:
 107°-158° byd 19 NM
 VOR unusable:
 098°-158° byd 19 NM blo 7,900'
