

POINT MUGU NAS (NAVAL BASE VENTURA CO) (NTD)(KNTD) NAS (ANG) O N UTC-8(-7DT)

LOS ANGELES

N34°07.16' W119°07.18'

H-4H, L-3E, 4G, 7B

13 B NOTAM FILE NTD Not insp.

DIAP, AD

RWY 03-21: H11102X200 (ASPH-CONC) PCN 47 R/C/W/T HIRL**RWY 03:** SALSF. OLS. PAPI(P4L)—GA 3.0° TCH 46'.**RWY 21:** MALS. OLS. PAPI(P4L)—GA 3.0° TCH 46'.**RWY 09-27:** H5502X200 (ASPH-CONC) PCN 51 F/B/W/T HIRL**ARRESTING GEAR/SYSTEM****RWY 03** HOOK E28(B) (2500')HOOK E28(B) (2502') **RWY 21****RWY 09** HOOK E28(B) (641')HOOK E28(B) (1252') **RWY 27****SERVICE:** LGT Rwy 03-21 4-light PAPI on left side of runway. Rwy 21 VGSi unusbl byd 6° left and byd 7° right of cntrlr.

Carrier deck lgt and mrkgs Rwy 27; IFLOLS Rwy 27. Rotg bcn not opr when arpt clsd. **MILITARY— A-Gear** Rwy 3-21 long-fld A-Gear rigged; short fld derigged, avbl 15 min PN. **JASU** 3(NCPC-105) 8(A/M47A-4) 9(GTC-85) **FUEL** J5, F24 (Jet AA) 5k gal trucks only, no hydrant fueling large/heavy tsnt acft exp rflg delays Hot pits not avbl for tsnt acft. **FLUID** SP LHOX LOX. **OIL** O-128-148 **TRAN ALERT/AIR TRML:** Opr 1400-0200Z† Mon-Thu; 1400-0100Z† altn Fri; clsd altn Fri, wkend and hol. Tsnt acft loading/offloading req outside publd hrs ctc afld mgr 805-989-8003/4737 for apvl. Lfd fleet svc (lavatory avbl); no potable water; not wet ice; no oxy). LOX ltd. Tsnt acft prkg extremely ltd. Min 24-hr prior notice rqr for acft with ordnance. Ordinance must be secured by det psnl or aircrew prior prior refueling. No tsnt maint/ltd svc. Tsnt acft maint/hgr space extremely ltd to non-existent. No de-icing avbl.

NOISE: Avoid populated areas when possible due to extreme noise sensitive area. Procedure in effect 0400-1600Z†. Expect Rwy 03 arr and Rwy 21 dep between 0400-0700Z† jets, and 0600-0700Z† all other acft, Mon-Sun, and federal holidays.

MILITARY REMARKS: Opr 1500-0700Z†. Rwy 03-21 first 500 ft Rwy 03 and first 4100 ft Rwy 21 conc; middle 6500 ft Rwy 03-21 is porous friction sfc. Rwy 09-27 first 1250 ft Rwy 27 conc; remainder Rwy 09-27 porous friction sfc. See FLIP AP/1 Supplementary Arpt Remarks and AP/1A. Bird watch cond severe: Wildlife activity on or imt above the active rwy or other specific location repg hight potential for strikes; supervision and aircrews must thoroughly evaluate mission need before conducting operations in areas under cond severe. Bird watch cond moderate: Wildlife activity near the active rwy or other specific locations repg increased potential for strikes; reqs increased vigilance by all agencies and supervisors and caution by aircrews. Bird watch cond low: Wildlife activity on or around the afld repg low potential for strikes. Wildlife hazard exists; pilots should report all bird and mammal sightings to twr or BOPS on freq 305.6. Phase I all dates not designated as phase II. Phase II eff 1 Oct thru 15 Apr; bird act is incrd dur these months due to the migratory season, the primary threat during these periods consists of large quantities and more frequent concentration of birds in all areas around the afld, and aircrews must be aware of heavy migratory fowl during these times. During Phase II, pilots can exp bird watch cond to be moderate or severe; takeoffs/landings within 90 min of offl SR/SS should only happen if it is mission essential; and if possible, training and frmn missions should avoid takeoff/landing with 90 min of the official SR/SS.

RSTD PPR for all tsnt acft. 72 hrs pn required. Acft that fail to arrive wi +/-30 min of ETA risk being cn unless prior cdn/update is made. Send all PPR reqs via email to nbvc_afm@us.navy.mil. Arpt hrs subj chg via NOTAM. AMC/NALO msn rqr flt advs or prior coord. Weekends, Oct-Jan, BASH support act removing waterfowl from the air in marsh areas S of Rwy 09-27 and w 700' of Rwy 21 edges/overrun. Vtol opr from any rwy, twy, apron prohibited exc declared emerg. 180 deg turns on asph rwy sections prohibited. Civ acft req valid/apvd Civil Aircraft Landing Permit (CALP); foreign acft req Navy Aircraft Landing Authorization Number (NALAN); ctc airfield mgr via email to nbvc_afm@us.navy.mil. New CALP rqs 30 days prior notice for coord/legal review. **CAUTION** Extreme mid-air potential due to high density VFR general aviation tfc in vicinity. Civilian arpt (Camarillo) 6 NM N uncontrolled 0500-1500Z† daily. High terrain to 1567' E of fld. Bird watch condition is moderate to severe, due to seasonal bird migration annually from Oct 1-Apr 30. Bird Hazard: Hang glider activity vicinity Round Mt 4 NM NE SR-SS. Arpt paratroop area active daily, 2-4 NM west of FNA crs Rwy 21 between 7-9 NM. Twy D clsd. Twy E clsd. Twy A2 open to prop and r/w, clsd to jet eng acft. E-28 A-Gear 25 ft from edge of rwy, aprxly 5 ft tall. **TFC PAT** Reduced rwy separation standards in effect USN/USMC acft. Rwy 21 dep do not commence turns until 500' and 1/2 NM offshore. Rwy 27 dep do not commence turns until 500'. **CSTMS/AG/IMG** Customs avbl Mon-Fri 1600-0700Z† with min 24 hr PN. Agriculture inspn/Intl waste removal not avbl; exp intl waste to remain ob to next apropr arpt. **MISC** Lrg/hvy 4-eng acft taxi with inbound engs only for fod mitigation. **ANG** Channel Islands ANGB PPR DSN 893-7577, C805-986-7577. Opr hrs 1400-0600Z†, clsd hol. Tsnt alert hrs 1500-2200Z† Mon-Fri, clsd Sat, Sun, and hol. PPR rqr for all tsnt acft on CIANGS Ramp only; use DSN 893-7577/7578, C805-986-7577/7578. Temporary waivers on ANG ramp: Fire hydrant bollards exist along the edge of the APN; modular airborne FFR sys pit taxi lines are not marked IAW reg; pits are only used during contingency ops, allowing acft to taxi close to fac to reload retardant; painted turn guidelines between parking spaces are not uniform (distances vary from 160.5 ft to 182.67 ft; current configuration places age equipment beneath the wing of turning acft, within the clear zone around the prop, and non-std markings—nose wheel markings and acft spot indication.

AIRPORT MANAGER: 805-986-7577**COMMUNICATIONS:** SFA ATIS 125.55 363.05 (Same as twr hrs)

® APP/DEP CON 128.65 307.275 (1500-0700Z†)

® L.A. CENTER APP/DEP CON 135.5 327.1 (0700-1500Z†)

TOWER 124.85 290.375 340.2 (1500-0700Z†, clsd holidays other times ctc L.A. Center App/Dep Con)**GND CON** 121.6 360.2 **CLNC DEL** 120.75 279.55**PMSV METRO** 386.35 OTS indef. **BASE OPS** 267.5 **HOLLYWOOD OPS** 305.6**CONTINUED ON NEXT PAGE**

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D svc 1500-0700Z†, clsd hol; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE HHR.

FILLMORE (VL) (L) VORTACW 112.5 FIM Chan 72 N34°21.40' W118°52.88' 205° 18.5 NM to fld. 2200/15E.

VOR unusable:

048°-058° byd 40 NM blo 6,000'
048°-058° byd 49 NM
070°-077° byd 40 NM
205°-217° byd 40 NM
267°-304° byd 40 NM
280°-315° byd 20 NM blo 11,000'
280°-315° byd 31 NM blo 14,000'
305°-315° byd 40 NM blo 18,000'
315°-360° byd 25 NM blo 14,000'
316°-323° byd 40 NM
324°-334° byd 40 NM blo 14,500'
324°-334° byd 70 NM
335°-043° byd 40 NM

TACAN AZIMUTH unusable:

265°-275° byd 15 NM
280°-310° byd 20 NM blo 14,000'
310°-360° byd 25 NM blo 14,000'

DME unusable:

265°-275° byd 15 NM
280°-315° byd 20 NM blo 11,000'
280°-315° byd 31 NM blo 14,000'
315°-360° byd 25 NM blo 14,000'

(L) TACAN Chan 43 NTD (110.6) N34°07.40' W119°07.32' at fld. 7/12E. NOTAM FILE NTD. TACAN unmonitored 0700-1500Z†.

TACAN AZIMUTH unusable:

060°-110° byd 15 NM blo 5,000'

DME unusable:

060°-110° byd 15 NM blo 5,000'

ILS/DME 109.3 I-NTD Chan 30 Rwy 03. Class IE. Unmonitored when ATCT closed. Glideslope unusable byd 8 NM.

ILS/DME 109.3 I-RRG Chan 30 Rwy 21. Class IE. Unmonitored when ATCT closed. LOC unusable byd 27° left of course. Glideslope unusable byd 7° left of course. DME unusable byd 27° left of course.

ASR/PAR (1500-0700Z†)

COMM/NAV/WEATHER REMARKS: Radar see Terminal FLIP for Radar Minima. Expanded Radar Svc—All fit conducted under positive control. Inbound acft not opr under ATC or Plead (132.425 306.6), ctc APP CON 25 NM out.

POINT REYES N38°04.79' W122°52.07' NOTAM FILE OAK.

SAN FRANCISCO

(VH) (DH) VORW/DME 113.7 PYE Chan 84 058° 15.2 NM to Gnosss Fld. 1340/17E.

H-3A, L-2F, 3A, A

VOR unusable:

000°-004° byd 40 NM
105°-114° byd 40 NM
202°-208° byd 40 NM
223°-228° byd 40 NM
255°-269° byd 40 NM
293°-301° byd 40 NM
311°-314° byd 40 NM
347°-352° byd 40 NM

POMONA N34°04.70' W117°47.22' NOTAM FILE RAL.

LOS ANGELES

(L) (L) VORTACW 110.4 POM Chan 41 at Brackett Fld. 1265/15E.

COPTER

DME unusable:

300°-045° byd 20 NM

VOR unusable:

280°-300° byd 20 NM blo 13,000'
300°-045° byd 20 NM

TACAN AZIMUTH unusable:

280°-300° byd 20 NM blo 14,000'
300°-045° byd 20 NM