

CONTINUED FROM PRECEDING PAGE

SERVICE: S4 **FUEL** JET A++ **OX** 1, 2 **LGT** Rwy thr lgts gated. Rwy 21L PAPI RRP and ILS RPI not coincidental. Rwy 03R and 21L ALSF-1 apch lgts NTE step 3 instst. Twy edge lgts adj to main aprn prkg rows 1 and 2 misg. **MILITARY—A-GEAR** All BAK-12 extn and in raised posn, rqr 30 min PN for removal. Rwy 03R-21L BAK-14 ops: both BAK-14 apch end and dep end will be in lowered pos. Avbl upon req for emer use only. Slow to 20 kts or less prior to dep end cable and taxi to far edge of cold side of rwy; taxi btn rwy edge and outermost BAK-14 bumper. **JASU** No starter unit for F4B, F4J, no starter probe for USN acft; 2(MA-1A) **FUEL** A++ . Fuel will not be ordered til acft is prk. **FLUID** W-Exp 2-3 hr delay, SP PRESAIR LHOX LOX. **OIL** O-123-128-132-133-148-156 SOAP **TRAN ALERT** Avbl Mon-Fri 1600Z-0400Z†, no quick turn Fri-Sun. No tsnt acft can arr/dep durg ACC quiet hrs (0630-1400Z†). No mil fleet svc avbl. Ltd tsnt svc avbl. Tsnt alert contract backshop maint support may rqr reimbursement and coord with contract officer. Due to large nr of tsnt and exer acft exp delays with tran alert.

NOISE: NS ABTMT quiet hrs in effect 0630-1400Z†. Dep climb above 3000' NA until DER.

MILITARY REMARKS: First 1320' Rwy 21R and 920' Rwy 03L grooved concrete, mid 7879' cntr 80' conc rmng asph. Rwy 03R-21L steep rising trn S and E of cntrln, LWR friction/reduced braking capability durg wet wx ops in brkg area 2500'-7000' fm Rwy 21L thr. Rwy 21L 9000'-10000' dist rmng mkr E side NA **RSTD** Sun & hol exp arr fmN; dep fm N winds perm; tfc pat twds E. Bird watch cond mod; ops rstd; tkof or ldg pmsn only when dep & arr avoid bird act; lcl IFR/VFR tfc pat not authorized. Bird watch cond svr; tkof or ldg not authorized wo OG/CC apl. Hot Cargo Pad unlit; rstd to daylight/VFR ops. Forward firing munitions in revetments 12, 13 & 25 not authorized. All tsnt acft must obtain PPR prior to arr. Refer to Nellis NOTAMS to id avbl airfield svcs window. PPR may be issued up to 7 days prior to, but NLT 48 hrs prior to sked arr. PPR for all exercise acft and with wingspans of 132.6' or larger acft ctc Nellis support center DSN 682-5250/5353. (Mon-Fri 1630-0130Z†). PPR for non-exercise acft smaller than 132.6' ctc AM ops DSN 682-4600, C702-652-4601. RON req good for one ngt only, dependent upon ramp space. Tran ftr, non exer acft prkg lmted to rows 45-46. Acft must adhere to PPR arr block +/- 30 mins of sked ldg. Mult apch NA durg RF/LFE or aft offi SS unless apvd by 57 WG SOF. Acft ptcpg in Nellis sponsored exers/large force exers rqr lcl sponsoring unit. The lcl sponsoring unit will coord maint, prkg, and svcs. PL-2 acft must bring own scy psnl and detail for all large force exers. Cstms & AG, ctc Nellis Support Cntr for acft with wingspans of 132.6' or lrgtr at DSN 682-5250 or ctc Base Ops for all other acft at DSN 682-4601 with 24 hr PN. Sun and hol tfc expc arr fm north, dep acft north winds pmted with tfc pat twd east (sunrise mt). Progressive taxi avbl. Acft with code 7 or hyr ctc PTD when 100 NM out. All inbd pax/cargo and DV acft must ctc command post (Raymond 22) on 381.300 NLT 30 mins prior to ldg. **CAUTION** Incr during BASH Phase II (Apr-May and Aug-Oct). Parachute Jumping. Rwy 03R-21L steep rising trn S and E of cntrln; Rwy 03R-21L provds btr BA than Rwy 03L-21R when wet. Use ctn for hydroplaning. Steeply rising trn commencing 2.7 NM east of Rwy 03L-21L cntrln up to 3359 MSL. Use ctn durg wet conds due to hydroplaning. Durg nml ops Rwy 03R-21L prvds btr BA than Rwy 03L-21R. Acft taxg on Twy D btn Twy F and Rwy 21R use ctn, 4 ft 8 inch hi dstc rmng sign lctd 125 ft north of Twy D cntrln. Hvy acft eng runs pmted on rwy; req must be sked thru airfield mgmt ops DSN 68204600. Due to FOD problem, 4 eng acft will taxi with outboard engs at idle pwr or shtdn if psbl jolly and tsnt helipads misg mandatory hold pos signs. rwy conds not rpted. Twy A east TACAN ck point sign nstd. **TFC PAT** Rect tfc pat 3000(1131), overhead tfc pat 3500(1631). **MISC** East side 9000' 1000' distance remaining markers Rwy 21L not avbl. Wx support H24-DSN 682-4744, C702-652-4744. Msn support wx per wing and exer sked typically 1300Z† Mon thru 0530Z† Fri, clsd weekend and hol, tsnt wx aft hr via Davis Monthan 25 OWS-D228-6598/6599, C520-228-6598/6599. Wx obs view of AER 03R/L rstd 190°-330° by flightline bldgs and fac and at ngt due to ramp lgt. Bldgs night flood lgts block the wx obsn view of the AER 03L-03R. No classified mtrl storage avbl at AM ops; classified must be stored in Nellis AFB command post. Tsnt acft shall communicate with Nellis ATC on UHF to max extent psbl due to hvy concentration of acft in the VFR pat. Rsrss will be applied to base asgnd/deployed acft.

AIRPORT MANAGER: 702-652-1110

COMMUNICATIONS: SFA ATIS 270.1 PTD 139.3 372.2 (Unreliable 085°-155° byd 35 NM at FL200, 315°-005° byd 40 NM at FL200, 230°-290° byd 55 NM at FL200.)

Ⓡ **APP CON** 118.125 124.95 273.55 291.725

TOWER 132.55 327.0 **GND CON** 121.8 275.8

Ⓡ **DEP CON** 135.1 350.225 **CLNC DEL** 120.9 289.4 (Opr 1400-0600Z†. Full svc avbl dur Nellis flying.)

ACC COMD POST (RAYMOND 22) 320.0 381.3 (381.3 Have quick timing avbl.) **ALCE AMC** 257.35 259.95 (Opr only dur Red Flag deployment/change over/redeployment and other exercises.) **PMSV METRO** 323.9 (Full svc avbl during wx ops hrs.

PMSV unrel 085-155 deg byd 35 NM at or blw FL 200, 315-005 deg byd 40 NM at or blw FL 200, 230-290 deg byd 55 NM at or blo FL 200.)

CONTINUED ON NEXT PAGE