SILVER CITY N32º38.26´ W108º09.66´ NOTAM FILE SVC. **ALBUQUERQUE L–5D**

(VL) (DH) VORW/DME 115.75 SVC Chan 104(Y) at Grant Co. 5423/13E.

VOR unusable:
228º–100º byd 40 NM
242º–252º byd 38 NM blo 12,100´
DME unusable:
242º–260º byd 35 NM blo 11,100´
305º–355º byd 29 NM blo 12,500´

SOCORRO MUNI (ONM)(KONM) 3 S UTC–7(–6DT) N34º01.35´ W106º54.19´ **ALBUQUERQUE H–4K, L–6F IAP**

4875 B NOTAM FILE ABQ

RWY 15–33: H5841X75 (ASPH) S–50, D–75, 2S–95 PCN 9 F/D/Y/T MIRL 0.9% up NW

RWY 15: PAPI(P2L)—GA 4.0º TCH 25´. Thld dsplcd 186´.

RWY 33: PAPI(P2L)—GA 4.0º TCH 26´. Thld dsplcd 182´.

RWY 06–24: H4590X60 (ASPH) PCN 3 F/D/Y/T MIRL 1.8% up W

SERVICE: FUEL 100LL **LGT** ACTVT PAPI Rwy 15; PAPI Rwy 33; MIRL Rwy 06–24 and 15–33—CTAF. MIRL Rwy 15–33 preset low intst; incr intst–CTAF.

AIRPORT REMARKS: Unattended. For emerg call 505–507–2800. 100LL avbl H24 credit card. Gate code 4850. Rwy 15 –40´ drop off 175´ fm thr both sides. Rwy 33 –20´ drop off 100´ fm thr both sides. Rwy 06–24 +4–8´ brush in primary sfc 50–125´ from cntrln south side and 60–125´ from cntrln north side. Rwy 06–24 4–8´ scattered brush in primary sfc 80–125´ from cntrln south side and 60–125´ from cntrln north side. West of intxn. Rwy 15–33 4–7´ brush in primary sfc 70–250´ fm cntrln west side, south of Rwy 06–24, 1–2´ brush 100–200´ fm cntrln east side of rwy.

AIRPORT MANAGER: 505-507-2800

WEATHER DATA SOURCES: AWOS–3 118.325 (575) 838–3993.

COMMUNICATIONS: CTAF/UNICOM 122.8

Ⓡ **ALBUQUERQUE CENTER APP/DEP CON** 124.325

CLEARANCE DELIVERY PHONE: For CD ctc Albuquerque ARTCC at 505-856-4561.

RADIO AIDS TO NAVIGATION: NOTAM FILE ABQ.

(VH) (H) VORTACW 116.8 ONM Chan 115 N34º20.33´ W106º49.23´ 179º 19.4 NM to fld. 4910/13E.

VOR unusable:
028º–038º byd 40 NM blo 18,000´
039º–043º byd 40 NM
044º–054º byd 40 NM blo 18,000´
055º–079º byd 40 NM
070º–079º byd 34 NM blo 14,000´
080º–170º byd 8 NM
188º–206º byd 40 NM
207º–217º byd 40 NM blo 20,000´
218º–223º byd 40 NM
240º–254º byd 40 NM
255º–265º byd 40 NM blo 12,000´
255º–265º byd 63 NM
266º–292º byd 40 NM
270º–285º byd 36 NM blo 14,000´
TACAN AZIMUTH unusable:
070º–080º byd 8 NM
270º–285º byd 22 NM
DME unusable:
070º–080º byd 27 NM blo 14,000´
080º–170º byd 8 NM
270º–285º byd 22 NM

