

**SCOTTSDALE** (SDL)(KSDL) 9 N UTC-7 N33°37.37' W111°54.63'

1510 B TPA—See Remarks NOTAM FILE SDL

**PHOENIX**

H-4J, L-5B, A

IAP, AD

**RWY 03-21:** H8249X100 (ASPH) S-45, D-75, 2S-95 MIRL

**RWY 03:** REIL. PAPI(P2L)—GA 4.0° TCH 59'. Thld dsplcd 740'. Tree. 0.7% up.

**RWY 21:** REIL. PAPI(P2L)—GA 4.0° TCH 40'. Thld dsplcd 400'. Hill. Rgt tfc. 0.9% down.

**RUNWAY DECLARED DISTANCE INFORMATION**


**RWY 03:** TORA-8249 TODA-8249 ASDA-7849 LDA-7110

**RWY 21:** TORA-8249 TODA-8249 ASDA-8069 LDA-7669

**SERVICE:** S4 FUEL 100LL, JET A1+ OX 1, 2, 3, 4 LGT When ATCT clsd ACTIVATE REIL Rwy 03 and Rwy 21; PAPI Rwy 03 and Rwy 21; MIRL Rwy 03-21—CTAF.

**NOISE:** Voluntary noise abatement curfew 0500-1300Z; noise sensitive area all quads; noise abatement—480-312-8478. Maint runup NA 0500-1400Z.

**AIRPORT REMARKS:** Attended continuously. Wildlife invof rwy. Mil arr 24 hr PPR—480-312-8478. Rwy 03-21 150 ft blast pad both ends. Ctc aviation director at 480-312-2321. Tran fee for acct 12,500 lbs or greater (based on max certificated ramp wgt). Tran over ngt parking fee. User fee arpt: Customs svcs avbl 1600Z to 0200Z; user fee must be prepaid online prior to arr. TGL NA 0430-1300Z. Midfield dep NA. Rwy 03 calm wind rwy. TPA-prop 2500(990); Jet 3000(1490); Helicopter 2000(490). D wgt thsd: cert max tkof wgt 7001-100,000 lb oprg abv 75,000 lb PPR—480-312-8478.



**AIRPORT MANAGER:** 480-312-7735

**WEATHER DATA SOURCES:** ASOS (480) 483-3049 ASOS bcsts on SDL ATIS freq (118.6) when SDL ATCT is clsd. LAWR8.

**COMMUNICATIONS:** CTAF 119.9 ATIS 118.6

**PHOENIX RCO** 122.2 (PRESCOTT RADIO)

® **PHOENIX APP/DEP CON** 120.7

**TOWER** 119.9 (1300-0400Z±) **GND CON** 121.6 **CLNC DEL** 124.8

**CLEARANCE DELIVERY PHONE:** For CD when ATCT clsd, ctc Phoenix Apch at 602-306-2565.

**AIRSPACE:** CLASS D svc 1300-0400Z; other times CLASS G.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE PRC.

**PHOENIX (H) VORTACW** 115.6 PXR Chan 103 N33°25.98' W111°58.21' 003° 11.8 NM to fld. 1184/12E.

VOR unusable:

000°-015° byd 33 NM blo 11,000'

015°-034° byd 33 NM blo 10,000'

090°-100° byd 15 NM blo 8,000'

185°-190° byd 30 NM blo 8,000'

185°-190° byd 38 NM blo 9,000'

190°-230° byd 20 NM blo 10,000'

345°-000° byd 33 NM blo 10,000'

345°-034° byd 10 NM blo 6,000'

345°-034° byd 20 NM blo 8,000'

TACAN AZIMUTH unusable:

000°-015° byd 33 NM blo 11,000'

015°-034° byd 33 NM blo 10,000'

090°-100° byd 15 NM blo 8,000'

185°-190° byd 30 NM blo 8,000'

185°-190° byd 38 NM blo 9,000'

190°-230° byd 20 NM blo 10,000'

345°-000° byd 33 NM blo 11,000'

345°-034° byd 10 NM blo 6,000'

345°-034° byd 20 NM blo 8,000'

DME unusable:

000°-015° byd 33 NM blo 11,000'

015°-034° byd 33 NM blo 10,000'

090°-100° byd 15 NM blo 8,000'

185°-190° byd 30 NM blo 8,000'

185°-190° byd 38 NM blo 9,000'

190°-230° byd 20 NM blo 10,000'

215°-315°

345°-000° byd 33 NM blo 11,000'

345°-034° byd 10 NM blo 6,000'

345°-034° byd 20 NM blo 8,000'

**COMM/NAV/WEATHER REMARKS:** Emerg frequency 121.5 not avbl at twr.